

Safety Data Sheet

Version 1.10
Revision Date 01/26/2015

SDS Number 300000000005
Print Date 06/06/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Argon (Refrigerated)

Chemical formula : Ar

Synonyms : Argon (refrigerated), Cryogenic Liquid Argon, Liquid Argon, LAR

Product Use Description : General Industrial

Manufacturer/Importer/Distributor : Air Products and Chemicals, Inc
7201 Hamilton Blvd.
Allentown, PA 18195-1501
GST No. 123600835 RT0001
QST No. 102753981 TQ0001

Telephone : 1-610-481-4911 Corporate
1-800-345-3148 Chemicals Cust Serv
1-800-752-1597 Gases/Electronics Cust Serv

Emergency telephone number (24h) : 800-523-9374 USA
+1 610 481 7711 International

2. HAZARDS IDENTIFICATION

GHS classification

Gases under pressure - Refrigerated liquefied gas
Simple Asphyxiant

GHS label elements

Hazard pictograms/symbols



Signal Word: Warning

Hazard Statements:

H281:Contains refrigerated gas; may cause cryogenic burns or injury.

Safety Data Sheet

Version 1.10

Revision Date 01/26/2015

SDS Number 300000000005

Print Date 06/06/2016

May displace oxygen and cause rapid suffocation.

Precautionary Statements:

- Prevention : P282:Wear cold insulating gloves/face shield/eye protection.
- Response : P315 :Get immediate medical advice/attention.
P336 :Thaw frosted parts with lukewarm water. Do not rub affected area.
- Storage : P403:Store in a well-ventilated place.

Hazards not otherwise classified

- Extremely cold liquid and gas under pressure.
Direct contact with liquid can cause frostbite.
Can cause rapid suffocation.
Avoid breathing gas.
Self contained breathing apparatus (SCBA) may be required.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Concentration (Volume)
Argon	7440-37-1	100 %

Concentration is nominal. For the exact product composition, please refer to Air Products technical specifications.

4. FIRST AID MEASURES

- General advice : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Keep eye wide open while rinsing.
- Skin contact : In case of frostbite, obtain medical treatment immediately. As soon as practical, place the affected area in a warm water bath- which has a temperature not to exceed 40 °C (105 °F). Do not rub frozen parts as tissue damage may result. Cover wound with sterile dressing.
- Ingestion : Ingestion is not considered a potential route of exposure.
- Inhalation : Move to fresh air. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. In

Safety Data Sheet

Version 1.10

Revision Date 01/26/2015

SDS Number 300000000005

Print Date 06/06/2016

case of shortness of breath, give oxygen.

Most important symptoms/effects - acute and delayed : Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : All known extinguishing media can be used.

Specific hazards : Spill will rapidly vaporize forming an oxygen deficient vapor cloud. Vapor cloud may obscure visibility. Do not direct water spray at container vent. Move away from container and cool with water from a protected position. Keep containers and surroundings cool with water spray.

Special protective equipment for fire-fighters : Wear self contained breathing apparatus for fire fighting if necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Evacuate personnel to safe areas. Ventilate the area. Monitor oxygen level. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

Environmental precautions : Prevent further leakage or spillage. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Do not discharge into any place where its accumulation could be dangerous.

Methods for cleaning up : Ventilate the area.

Additional advice : If possible, stop flow of product. Increase ventilation to the release area and monitor oxygen level. Vapor cloud may obscure visibility. Do not spray water directly at leak. If leak is from cylinder or cylinder valve, call the Air Products emergency telephone number. If the leak is in the user's system, close the cylinder valve and safely vent the pressure before attempting repairs.

7. HANDLING AND STORAGE

Handling

Know and understand the properties and hazards of the product before use. Only experienced and properly instructed persons should handle compressed gases/cryogenic liquids. Before using the product, determine its identity by reading the label. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. Before connecting the container, check the complete gas system for suitability, particularly for pressure rating and materials. Before connecting the container for use, ensure that back feed from the system into the container is prevented. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. If user experiences any difficulty operating cylinder valve discontinue

Safety Data Sheet

Version 1.10

Revision Date 01/26/2015

SDS Number 300000000005

Print Date 06/06/2016

use and contact supplier. Do not remove or interchange connections. Ensure the complete gas system has been checked for leaks before use. Prevent entrapment of cryogenic liquid in closed systems not protected with relief device. A small quantity of liquid produces large volumes of vaporized gas at atmospheric pressure. Containers used in shipment, storage, and transfer of cryogenic liquid are specially designed, well-insulated containers equipped with a pressure relief device and valves to control pressure. Under normal conditions, these containers will periodically vent product to limit pressure buildup. Ensure that the container is in a well-ventilated area to avoid creating an oxygen-deficient atmosphere. Use adequate pressure relief in systems and piping to prevent pressure buildup; liquid in a closed container can generate extremely high pressures when vaporized by warming. Employ suitable pressure regulating devices on all containers when the gas is being emitted to systems with lower pressure rating than that of the container. Only transfer lines designed for cryogenic liquids shall be used. Do not subject containers to abnormal mechanical shock. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. When doubt exists as to the correct handling procedure for a particular gas, contact the supplier.

Storage

Use a back flow preventative device in the piping. Do not change or force fit connections. Always keep container in upright position. Open/close valve slowly. Close when not in use. Wear Safety Eye Protection. Check Safety Data Sheet before use. Do not allow storage temperature to exceed 50°C (122°F). Containers should be stored in a purpose build compound which should be well ventilated, preferably in the open air. Full containers should be stored so that oldest stock is used first. Do not store in a confined space. Full and empty cylinders should be segregated. Store containers in location free from fire risk and away from sources of heat and ignition. Return empty containers in a timely manner. Stored containers should be periodically checked for general condition and leakage. Protect containers stored in the open against rusting and extremes of weather. Containers should not be stored in conditions likely to encourage corrosion. Cryogenic containers are equipped with pressure relief devices to control internal pressure. Under normal conditions these containers will periodically vent product. All vents should be piped to the exterior of the building. Observe all regulations and local requirements regarding storage of containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures

Natural or mechanical to prevent oxygen deficient atmospheres below 19.5% oxygen.
Keep self contained breathing apparatus readily available for emergency use.

Personal protective equipment

- Respiratory protection : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmosphere.
Air purifying respirators will not provide protection. Users of breathing apparatus must be trained.
- Hand protection : Wear working gloves when handling gas containers.
If the operation involves possible exposure to a cryogenic liquid, wear loose fitting thermal insulated or cryo-gloves.
Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety glasses recommended when handling cylinders.
Protect eyes, face and skin from liquid splashes.

Safety Data Sheet

Version 1.10

Revision Date 01/26/2015

SDS Number 300000000005

Print Date 06/06/2016

Wear goggles and a face shield when transfilling or breaking transfer connections.

Skin and body protection : Never allow any unprotected part of the body to touch uninsulated pipes or vessels which contain cryogenic fluids. The extremely cold metal will cause the flesh to stick fast and tear when one attempts to withdraw from it. Safety shoes are recommended when handling cylinders.

Special instructions for protection and hygiene : Ensure adequate ventilation, especially in confined areas.

Remarks : Simple asphyxiant.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquefied gas. Colorless.

Odor : No odor warning properties.

Odor threshold : No data available.

pH : Not applicable.

Melting point/range : -308 °F (-189 °C)

Boiling point/range : -303 °F (-186 °C)

Flash point : Not applicable.

Evaporation rate : Not applicable.

Flammability (solid, gas) : Refer to product classification in Section 2

Upper/lower explosion/flammability limit : No data available.

Vapor pressure : Not applicable.

Water solubility : 0.067 g/l

Relative vapor density : 1.38 (air = 1) Heavier than air.

Relative density : 1.4 (water = 1)

Partition coefficient (n-octanol/water) : Not applicable.

Auto-ignition temperature : No data available.

Safety Data Sheet

Version 1.10

Revision Date 01/26/2015

SDS Number 300000000005

Print Date 06/06/2016

Decomposition temperature : No data available.
Viscosity : Not applicable.
Molecular Weight : 40 g/mol

10. STABILITY AND REACTIVITY

Chemical Stability : Stable under normal conditions.
Conditions to avoid : No data available.
Materials to avoid : Carbon steel.
Hazardous decomposition products : No data available.
Possibility of hazardous Reactions/Reactivity : No data available.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Likely routes of exposure

Effects on Eye : Contact with liquid may cause cold burns/frostbite.
Effects on Skin : Contact with liquid may cause cold burns/frostbite. May cause severe frostbite.
Inhalation Effects : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves.
Ingestion Effects : Ingestion is not considered a potential route of exposure.
Symptoms : Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.

Acute toxicity

Acute Oral Toxicity : No data is available on the product itself.
Inhalation : No data is available on the product itself.
Acute Dermal Toxicity : No data is available on the product itself.
Skin corrosion/irritation : No data available.

Safety Data Sheet

Version 1.10

Revision Date 01/26/2015

SDS Number 300000000005

Print Date 06/06/2016

Serious eye damage/eye irritation : No data available.

Sensitization. : No data available.

Chronic toxicity or effects from long term exposures

Carcinogenicity : No data available.

Reproductive toxicity : No data is available on the product itself.

Germ cell mutagenicity : No data is available on the product itself.

Specific target organ systemic toxicity (single exposure) : No data available.

Specific target organ systemic toxicity (repeated exposure) : No data available.

Aspiration hazard : No data available.

Delayed and Immediate Effects and Chronic Effects from Short and Long Term Exposure

Not applicable.

12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Aquatic toxicity : Not applicable.

Toxicity to other organisms : Not applicable.

Persistence and degradability

Biodegradability : No data is available on the product itself.

Mobility : No data available.

Bioaccumulation : No data is available on the product itself.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused : Return unused product in original cylinder to supplier. Contact supplier if

Safety Data Sheet

Version 1.10

Revision Date 01/26/2015

SDS Number 300000000005

Print Date 06/06/2016

products guidance is required.
Contaminated packaging : Return cylinder to supplier.

14. TRANSPORT INFORMATION

DOT

UN/ID No. : UN1951
Proper shipping name : Argon, refrigerated liquid
Class or Division : 2.2
Label(s) : 2.2
Marine Pollutant : No

IATA

UN/ID No. : UN1951
Proper shipping name : Argon, refrigerated liquid
Class or Division : 2.2
Label(s) : 2.2
Marine Pollutant : No

IMDG

UN/ID No. : UN1951
Proper shipping name : ARGON, REFRIGERATED LIQUID
Class or Division : 2.2
Label(s) : 2.2
Marine Pollutant : No

TDG

UN/ID No. : UN1951
Proper shipping name : ARGON, REFRIGERATED LIQUID
Class or Division : 2.2
Label(s) : 2.2
Marine Pollutant : No

Further Information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact an Air Products customer service representative.

15. REGULATORY INFORMATION

Toxic Substance Control Act (TSCA) 12(b) Component(s):

Safety Data Sheet

Version 1.10

Revision Date 01/26/2015

SDS Number 300000000005

Print Date 06/06/2016

None.

Country	Regulatory list	Notification
USA	TSCA	Included on Inventory.
EU	EINECS	Included on Inventory.
Canada	DSL	Included on Inventory.
Australia	AICS	Included on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.
Japan	ENCS	Included on Inventory.

EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification
Acute Health Hazard

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

16. OTHER INFORMATION

NFPA Rating

Health : 3
Fire : 0
Instability : 0

HMIS Rating

Health : 3
Flammability : 0
Physical hazard : 1

Prepared by : Air Products and Chemicals, Inc. Global EH&S Product Safety Department

Telephone : 1-610-481-4911 Corporate
1-800-345-3148 Chemicals Cust Serv
1-800-752-1597 Gases/Electronics Cust Serv

Preparation Date : 06/06/2016

For additional information, please visit our Product Stewardship web site at
<http://www.airproducts.com/productstewardship/>

Safety Data Sheet

Version 1.10

Revision Date 01/26/2015

SDS Number 300000000005

Print Date 06/06/2016
